

ISB 23124 EKW33+H3124 spherical roller bearings

Browse ISB 23124 EKW33+H3124 spherical roller bearings Categories in the 47x25x12 Size (mm) Manufacturers Online Free. 47 Bore Diameter (mm) including .

Size (mm)	47x25x12
Bore Diameter (mm)	47
Outer Diameter (mm)	25
Width (mm)	12
d	25 mm
D	47 mm
B	12 mm
d2	29.7 mm
D2	42.2 mm
r1,2 – min.	0.6 mm
da – min.	28.2 mm
da – max.	29.5 mm
Da – max.	43.8 mm
ra – max.	0.6 mm
Basic dynamic load rating – C	11.9 kN
Basic static load rating – C0	6.6 kN
Fatigue load limit – Pu	0.275 kN
Reference speed	40000 r/min
Limiting speed	22000 r/min
Calculation factor – kr	0.025

Calculation factor – f0	14.3
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.066
EAN	7316572070772
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Silicon Nitride Rolling Element Electrical Insulated
Cage Material	Polyamide
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	25MM Bore; 47MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Low Friction NBR Seal Hybrid Silicon Nitride Rolling Element WT Standard Grease
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Manufacturer Item Number	6005-2RSLTN9/HC5C3WT
Weight / LBS	0.073
Inner Race Width	0 Inch 0 Millimeter
Bore	0.984 Inch 25 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
d2 ≈	29.7 mm
D2 ≈	42.2 mm
r1,2 min.	0.6 mm
da min.	28.2 mm
da max.	29.5 mm
Da max.	43.8 mm
ra max.	0.3 mm
Basic dynamic load rating C	11.9 kN
Basic static load rating C0	6.55 kN
Fatigue load limit Pu	0.275 kN
Calculation factor kr	0.025
Calculation factor f0	14.3
Mass bearing	0.073 kg