

# ISB 241/600 EK30W33+A0H241/600 spherical roller bearings

The online REXNORD Manufacturer Name ISB 241/600 EK30W33+A0H241/600 spherical roller bearings parts store gives 0.0 Inventory you immediate access to a selection of more N/A Minimum Buy Quantity than 1.4 million new, used, remanufactured.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | REXNORD                  |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 49.032                   |
| EAN                       | 0793699319422            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 4                        |
| Mounting Method           | Concentric Collar        |
| Housing Style             | 4 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Iron                |
| Expansion / Non-expansion | Non-expansion            |
| Mounting Bolts            | 1 Inch                   |
| Relubricatable            | Yes                      |
| Insert Part Number        | 5407YU                   |
| Seals                     | Clearance Seal           |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Inch                     |

|                               |   |
|-------------------------------|---|
| Other Features                | Double Row   Heavy Duty   Double Collar   With Set Screw                                  |
| Long Description              | 4 Bolt Pillow Block; 4-7/16" Bore; 5-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | ZP5407YF78  |
| Manufacturer Internal Number  | 0131942   |
| Weight / LBS                  | 108   |
| B                             | 5.75 Inch   146.05 Millimeter   |
| Actual Bolt Center to Center  | 14.8 Inch   375Millimeter   |
| d                             | 4.438 Inch   112.725 Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| D                             | 6.25 Inch   158.75 Millimeter   |
| Nominal Bolt Center to Center | 14.8 Inch   375 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |