

ISB 241/750 EK30W33+A0H241/750 spherical roller bearings

Manufacturers of all are represented in 30 Bore Diameter (mm) our partial list of clients. Contact Gary for a complete ISB 241/750 EK30W33+A0H241/750 spherical roller bearings steelonPTFE fabric, sealed Bearing Type – steel-on-PTFE fabric, sealed list of clients and projects.

Bore Diameter (mm)	30
Width (mm)	22
Bearing Type – steel-on-PTFE fabric, sealed	steelonPTFE fabric, sealed
Bore Dia (d)	30.0000
Width (B)	22.0000
Radius (min) (rs)	0.600
Dynamic Load Rating (Cr)	110,000
Static Load Rating (Cor)	110,000
Spherical Diameter (dk or Dk)	40.700
Mis-alignment Angle (a deg.)	6
Thread Length (l1)	56.000
Bore Center to End of Rod (h)	110.000
Rod Overall Length (l2)	146.500
Rod End Thickness (C1)	20.000
Bore Center to Body (l7)	38
Thread Size (G)	M30 X 3
Rod End Width (d2)	73.000
Body Dia. (d3)	42.000

Body End Dia. (d4)	50.000
Body End Width (l5)	15.000
Body End Flats (W)	46.000
Weight (g)	980.00
Material – Body – Carbon steel-zinc plated, Ball – Hardened chrome steel-chrome plated, Liner	PTFE fabric material