

# ISB 24132 EK30W33+AH24132 spherical roller bearings

ISB 24132 EK30W33+AH24132 spherical roller bearings  
Manufacturers 10x35x11 Size (mm) , 35 Outer Diameter (mm)  
Online 10 Bore Diameter (mm) Wholesale Suppliers !

Size (mm)	10x35x11
Bore Diameter (mm)	10
Outer Diameter (mm)	35
Width (mm)	11
d	10 mm
D	35 mm
B	11 mm
C	11 mm
Angle ( $\alpha$ )	25 °
a	12 mm
r min.	0,6 mm
r1 min.	0,3 mm
da min.	14,5 mm
db min	12,5 mm
ra max.	0,6 mm
Weight	0,04 Kg
Basic dynamic load rating (C)	10,1 kN
Basic static load rating (C0)	4,95 kN
(Grease) Lubrication Speed	26 000 r/min
Contact angle $\alpha$	30 °
rs min	0.6 mm
r1s min	0.3 mm

Mass	0.04 kg
Dynamic load, C	10.1 kN
Static load, C0	4.95 kN
Fatigue limit load, Cu	0.23 kN
Nlim (oil)	34,000 rpm
Nlim (grease)	26,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	14.5 mm
Da max	30.5 mm
Db max	32.5 mm
r1a max	0.3 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.054
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)

Inch – Metric	Metric
Long Description	10MM Bore; 35MM Outside Diameter; 11MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Bore	0.394 Inch   10 Millimeter
Width	0.433 Inch   11 Millimeter
Outside Diameter	1.378 Inch   35 Millimeter