

# ISB 30210J/DF tapered roller bearings

We Provide Extensive ISB 30210J/DF tapered roller bearings Selection And Competitive Wholesale 0.0 Inventory Pricing.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 27.24  |
| EAN                       | 0883450222303  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Square Flange Block   |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Double Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | No Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Square Flange Block;<br>3-15/16" Bore; 12.2" Bolt<br>Circle; 8.63" Bolt Spacing; 1<br>P |

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Other Features                        | Double Row   Double Nut            |
| UNSPSC                                | 31171501                           |
| Harmonized Tariff Code                | 8483.20.40.80                      |
| Noun                                  | Bearing                            |
| Keyword String                        | Flanged                            |
| Manufacturer Item Number              | QVVF22V315SC                       |
| Weight / LBS                          | 60                                 |
| d                                     | 3.938 Inch   100.025<br>Millimeter |
| Nominal Bolt Circle Diameter<br>Round | 12.2 Inch   309.9 Millimeter       |
| Bolt Spacing                          | 8.63 Inch   219.202<br>Millimeter  |
| D                                     | 4.99 Inch   126.746<br>Millimeter  |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter              |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter              |