

ISB 306/682X4-3 tapered roller bearings

ISB 306/682X4-3 tapered roller bearings Engineering Calculator , 0.0 Inventory Manufacturing Service . Get Your Free.

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | ABB MOTORS AND MECHANICAL INC |
| Minimum Buy Quantity | N/A |
| Weight | 27.24 |
| EAN | 0782475035953 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 4 Bolt Pillow Block |
| Rolling Element | Tapered Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | DU-SD-208 |
| Seals | Dual Piston Ring Seal |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Double Row Special Duty |
| Long Description | 4 Bolt Pillow Block; 2-1/2" Bore; 4" Base to Center Height; Tapered Adapter Sleeve Mount; |
| UNSPSC | 31171511 |

| | |
|-------------------------------|---------------------------------|
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | P4B-SD-208 SPECIAL DUTY |
| Manufacturer Internal Number | 066244 |
| Weight / LBS | 60 |
| Nominal Bolt Center to Center | 10.8 Inch 273.1 Millimeter |
| d | 2.5 Inch 63.5 Millimeter |
| Bolt Spacing Maximum | 11.625 Inch 295.275Millimeter |
| B | 4 Inch 101.6 Millimeter |
| D | 5.063 Inch 128.59 Millimeter |
| Bolt Spacing Minimum | 9.875 Inch 250.83Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |