

# ISB 32022X/DF tapered roller bearings

How do you find the ISB 32022X/DF tapered roller bearings N/A  
Minimum Buy Quantity specification? Manufacturers Online 0.0  
Inventory Free check  TIMKEN Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 14.528  |
| EAN                       | 0883450034326   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22218   |
| Seals                     | Triple Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>85MM Bore; 236.2MM Bolt Circle;<br>168.275MM Bolt Spacing; 1 Piece<br>Solid |

|                                       |  |
|---------------------------------------|--|
| Other Features                        | Double Row   Double Collar  <br>With Set Screw |
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Weight / LBS                          | 32   |
| Nominal Bolt Circle Diameter<br>Round | 9.3 Inch   236.2 Millimeter                    |
| d                                     | 3.346 Inch   85 Millimeter                     |
| Bolt Spacing                          | 6.625 Inch   168.275 Millimeter                |
| Cartridge Pilot Depth                 | 1.31 Inch   33.274 Millimeter                  |
| Cartridge Pilot Diameter              | 7.375 Inch   187.32 Millimeter                 |
| D                                     | 5.18 Inch   131.572 Millimeter                 |