

# ISB 3207 A angular contact ball bearings

Enjoy 30 Bore Diameter (mm) High Margins on Competitive Pricing.Great 71 mm Da Wholesale Products at Low 30 mm d Costs.

Bore Diameter (mm)	30
d	30 mm
Da	71 mm
A1	2.5 mm
B1	35.7 mm
G	10 mm
H	112 mm
H1	– mm
J	90,5 mm
L	84 mm
N	10,5 mm
T	29,2 mm
A2	9.5 mm
Weight	0,46 Kg
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,2 kN
Housing material	Pressed steel
Da min.	67 mm
B4	5.95 mm
s1	26.7 mm
Basic dynamic load rating C	19.5 kN
Basic static load rating C0	11.2 kN

Fatigue load limit Pu	0.475 kN
Limiting speed	6300 r/min
Mass bearing unit	0.47 kg
Thread grub screw G2	M8x1
Hexagonal key size for grub screw N	4 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	PFT 62
Bearing	YET 206