

# ISB 32230J/DF tapered roller bearings

ISB 32230J/DF tapered roller bearings Industries and Applications ? We sell discount 0.0 Inventory online as well as cheap machinery parts.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 3.632   |
| EAN                       | 0662327111199   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | B22419HL  |
| Seals                     | Floating Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Single Collar  <br>Extended Inner Race   With Set<br>Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 1-3/16" Bore; 1-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | PEB22419H   |
| Manufacturer Internal Number  | 5811119   |
| Weight / LBS                  | 6   |
| D                             | 2.688 Inch   68.275 Millimeter  |
| Nominal Bolt Center to Center | 4.8 Inch   121 Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| Actual Bolt Center to Center  | 4.8 Inch   121Millimeter  |
| d                             | 1.188 Inch   30.175 Millimeter  |
| B                             | 1.75 Inch   44.45 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |