

# ISB 32236 tapered roller bearings

ISB 32236 tapered roller bearings with easy-to-use 0.0 Inventory parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

|                            |  |
|----------------------------|--|
| Inventory                  | 0.0  |
| Manufacturer Name          | SKF  |
| Minimum Buy Quantity       | N/A  |
| Weight                     | 6.544  |
| EAN                        | 7316577007520  |
| Product Group              | B00308   |
| Rolling Element            | Ball Bearing   |
| Thrust Bearing             | Yes  |
| Single or Double Direction | Double Direction   |
| Banded                     | No   |
| Cage Material              | Steel  |
| Precision Class            | ABEC 1   ISO P0  |
| Component Description      | Roller Assembly Plus Raceways  |
| Optional Components        | Order U317 Seating Washer Separately   |
| Other Features             | Double Row   |
| Long Description           | 70MM Bore 1; 88MM Bore 2; 150MM Outside Diameter; 95MM Height; Ball Bearing; Double Direction; Not B |
| Inch – Metric              | Metric   |
| UNSPSC                     | 31171507   |
| Harmonized Tariff Code     | 8482.10.50.08  |

|                                     |                             |
|-------------------------------------|-----------------------------|
| Noun                                | Bearing                     |
| Keyword String                      | Ball Thrust                 |
| Manufacturer Item Number            | 54317                       |
| Weight / LBS                        | 14.414                      |
| D                                   | 5.906 Inch   150 Millimeter |
| Bore 2                              | 3.465 Inch   88 Millimeter  |
| Height                              | 3.74 Inch   95 Millimeter   |
| Overall Height with Aligning Washer | 0 Inch   0 Millimeter       |
| Bore 1                              | 2.756 Inch   70 Millimeter  |
| bore diameter:                      | 70 mm                       |
| static load capacity:               | 405 kN                      |
| outside diameter:                   | 150 mm                      |
| dynamic load capacity:              | 174 kN                      |
| overall width:                      | 105 mm                      |
| maximum rpm:                        | 1500 RPM                    |
| thrust bearing type:                | Double-Direction            |
| cage material:                      | Steel                       |
| outside diameter design:            | Straight                    |
| fillet radius:                      | 1.5 mm                      |
| separable or banded:                | Separable                   |
| series:                             | 543                         |
| precision rating:                   | ABEC 1 (ISO Class Normal)   |