

# ISB 51430 M thrust ball bearings

Browse ISB 51430 M thrust ball bearings 0.0 Inventory Categories in the Manufacturers Online N/A Minimum Buy Quantity Free. including .

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.235   |
| EAN                       | 0808250145478   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Nickel Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UC207-23MZ2   |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 2 Bolt Flange Block; 1-7/16" Bore; 5.1" Bolt Circle; 5-1/8" Bolt Spacing; 1 Piece Sol |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Single Row   Spherical   Normal Duty   Zinc Coated Insert   Has Slinger |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.40   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Manufacturer Item Number           | UCFT207-23NPMZ2   |
| Weight / LBS                       | 3.08  |
| d                                  | 1.438 Inch   36.525 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter   |
| D                                  | 1.689 Inch   42.9 Millimeter  |
| Nominal Bolt Circle Diameter Round | 5.1 Inch   130 Millimeter   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |
| Bolt Spacing                       | 5.125 Inch   130.18 Millimeter  |