

ISB 6202-ZZNR deep groove ball bearings

ISB 6202-ZZNR deep groove ball bearings Needs Analysis , Manufacturing Service 66.675 mm da . Get Your Free.

da	66.675 mm
Da	140 mm
Ca	42.799 mm
A1	88.9 mm
A2	126.603 mm
ba	30.163 mm
H	169.863 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.181 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	33.337 mm
Housing	FSAF 516
Bearing	1216 K
Adapter sleeve assembly	SNW 16×2.5/8
Stabilizing ring	2 x SR-1616

Labyrinth ring	2 x LOR 43
End plug (suffix Y)	EPR 8
Bearing limiting speed	6000 r/min
P60°	60.5 kN
P90°	36 kN
P120°	21.8 kN
P150°	19.6 kN
P180°	23.1 kN
Pa	6.23 kN
Mass pillow block	16.8 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	175.77 g