

ISB 626RS deep groove ball bearings

ISB 626RS deep groove ball bearings Needs Analysis , 71.438 mm da Manufacturing Service 69.799 mm Ca . Get 180 mm Da Your Free.

da	71.438 mm
Da	180 mm
Ca	69.799 mm
A1	111.125 mm
A2	231.775 mm
S	4.763 mm
ba	48.419 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	25.4 mm
R1	66.675 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/8 NPT
h	44.45 mm
Housing	SAF 617
Bearing	22317 EK
Adapter sleeve assembly	SNW 117×2.13/16

Stabilizing ring	SR-20-17
Taconite seal	TER 182
End plug (suffix Y)	EPR 10
Max. speed for Taconite seal	1050 r/min
P60°	94.3 kN
P90°	56.5 kN
P120°	35.6 kN
P150°	32 kN
P180°	38.3 kN
Pa	15.3 kN
Mass pillow block	33.9 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g