

ISB 6305-Z deep groove ball bearings

ISB 6305-Z deep groove ball bearings Manufacturers Mounted Bearing Engineering Group , Online Wholesale Metric Shaft Size Type Suppliers !

| | |
|-------------------------|-------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 60 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QAAFL13A060SB |
| Locking Style | Double Concentric |
| Weight | 17.0 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450145992 |
| Dimension BC | 6.75 in |
| Dimension C | 4 in |
| Dimension D | 5.750 in |
| Dimension E | 4.77 in |
| Dimension F | 6.19 in |
| Dimension H | 1.00 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension L Exp | 3.59 in |
| Dimension L Fix | 3.51 in |
| Dimension M | 2.15 in |
| Dimension N | 2.860 in |
| Dimension RAA | 0.79 in |
| Dimension SAA | 4.3 in |
| C0 – Static Load | 48600 lb |

| | |
|-------------------------------------|-----------|
| C – Dynamic Load (Basic) | 46400 lb |
| e – Geometry Factor | 0.25 |
| Y1 – Geometry Factor | 2.69 |
| Y2 – Geometry Factor | 4.00 |
| Oil Lubrication – M/N Seal | 1800 rpm |
| Oil Lubrication – T Seal | 3200 rpm |
| Oil Lubrication – B/C/O Seal | 1500 rpm |
| Grease Lubrication – M/N Seal | 1800 rpm |
| Grease Lubrication – T Seal | 2800 rpm |
| Grease Lubrication – B/C/O Seal | 1500 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0016 |
| Eng Internal Radial Clearance – Max | 0.0026 |
| Pre Install Clearance Min | 0.0016 in |
| Pre Install Clearance Max | 0.0026 in |