

ISB CRBC 30040 thrust roller bearings

High Quality ISB CRBC 30040 thrust roller bearings. 11 mm B Competitive 10 mm d Pricing. Accept Small Order. Easy and Fast Shipping.

d	10 mm
D	35 mm
B	11 mm
rs min	0.6 mm
Radial clearance class	CN
Mass	0.05 kg
Dynamic load, C	8.2 kN
Static load, C ₀	3.5 kN
Fatigue limit load, C _u	0.16 kN
f ₀	11.4
N _{lim} (grease)	16,000 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.35 Hz
Characteristic rolling element frequency, BSF	2.94 Hz
Characteristic outer ring frequency, BPF ₀	2.08 Hz
Characteristic inner ring frequency, BRFI	3.92 Hz
da min	14 mm
da max	17 mm

Da max	31 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.053
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	10MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	0.117
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.433 Inch 11 Millimeter
Bore	0.394 Inch 10 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter