

# ISB FCDP 88124450 cylindrical roller bearings

Online shopping ISB FCDP 88124450 cylindrical roller bearings from a great selection at Store. ... Accessories. 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 11.804   |
| EAN                       | 0883450114523  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 16 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22212  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut   SN Style   |
| Long Description          | 2 Bolt Pillow Block; 2-1/4" Bore; 2-3/4" Base to Center Height; V Lock Mount; Spherical Ro |

|                               |                              |
|-------------------------------|------------------------------|
| UNSPSC                        | 31171511                     |
| Harmonized Tariff Code        | 8483.20.40.80                |
| Noun                          | Bearing                      |
| Keyword String                | Pillow Block                 |
| Weight / LBS                  | 26                           |
| D                             | 3.15 Inch   80 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter         |
| d                             | 2.25 Inch   57.15 Millimeter |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter  |
| Bolt Spacing Maximum          | 8.504 Inch   216Millimeter   |
| B                             | 2.75 Inch   69.85 Millimeter |
| Bolt Spacing Minimum          | 7.205 Inch   183Millimeter   |