

ISB GE 95 XS K plain bearings

100% Authentic. 42x20x12 Size (mm) ISB GE 95 XS K plain bearings 20 Outer Diameter (mm) Highest Quality. Certified 42 Bore Diameter (mm) Supplier.

Size (mm)	42x20x12
Bore Diameter (mm)	42
Outer Diameter (mm)	20
Width (mm)	12
d	20 mm
D	42 mm
B	12 mm
d1	27.1 mm
d2	27.1 mm
D1	34.8 mm
r1,2 – min.	0.6 mm
r3,4 – min.	0.3 mm
a	13.3 mm
da – min.	23.2 mm
db – min.	23.2 mm
Da – max.	38.8 mm
Db – max.	40 mm
ra – max.	0.6 mm
rb – max.	0.3 mm
dn	28.4 mm
Basic dynamic load rating – C	8.3 kN
Basic static load rating – C0	4.2 kN
Fatigue load limit – Pu	0.173 kN

Limiting speed for grease lubrication	45000 r/min
Limiting speed for oil lubrication	70000 mm/min
Ball – Dw	6.35 mm
Ball – z	12
Gref	0.9 cm ³
Calculation factor – e	0.68
Calculation factor – Y2	1.41
Calculation factor – Y0	0.76
Calculation factor – X2	0.67
Calculation factor – Y1	0.92
Preload class A – GA	50 N
Preload class B – GB	100 N
Preload class C – GC	200 N
Preload class D – GD	400 N
Calculation factor – f	1.03
Calculation factor – f1	0.99
Calculation factor – f2A	1
Calculation factor – f2B	1.02
Calculation factor – f2C	1.05
Calculation factor – f2D	1.08
Calculation factor – fHC	1.02
Preload class A	60 N/micron
Preload class B	77 N/micron
Preload class C	100 N/micron
Preload class D	133 N/micron
r _{1,2} min.	0.6 mm
r _{3,4} min.	0.3 mm
da min.	23.2 mm
db min.	23.2 mm

Da max.	38.8 mm
Db max.	40 mm
ra max.	0.6 mm
rb max.	0.3 mm
Basic dynamic load rating C	8.32 kN
Basic static load rating C0	4.15 kN
Fatigue load limit Pu	0.173 kN
Attainable speed for grease lubrication	45000 r/min
Attainable speed for oil-air lubrication	70000 r/min
Ball diameter Dw	6.35 mm
Number of balls z	12
Reference grease quantity Gref	0.9 cm ³
Preload class A GA	50 N
Static axial stiffness, preload class A	60 N/μm
Preload class B GB	100 N
Static axial stiffness, preload class B	77 N/μm
Preload class C GC	200 N
Static axial stiffness, preload class C	100 N/μm
Preload class D GD	400 N
Static axial stiffness, preload class D	133 N/μm
Calculation factor f	1.03
Calculation factor f1	0.99
Calculation factor f2A	1
Calculation factor f2B	1.02
Calculation factor f2C	1.05
Calculation factor f2D	1.08
Calculation factor fHC	1.02
Calculation factor e	0.68
Calculation factor (single, tandem) Y2	0.87

Calculation factor (single, tandem) Y0	0.38
Calculation factor (single, tandem) X2	0.41
Calculation factor (back-to-back, face-to-face) Y1	0.92
Calculation factor (back-to-back, face-to-face) Y2	1.41
Calculation factor (back-to-back, face-to-face) Y0	0.76
Calculation factor (back-to-back, face-to-face) X2	0.67
Mass bearing	0.06 kg