

# ISB GX 360 CP plain bearings

Shop ISB GX 360 CP plain bearings huge online discount inventory. and Import machinery parts your 0.0 Inventory car needs with Free Shipping and Free Extended Warranty.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 31.326  |
| EAN                       | 0883450114844   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | V Lock  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 24 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | 22222   |
| Seals                     | Teflon Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Single Nut   SN Style  |
| Long Description          | 2 Bolt Pillow Block; 3-3/4" Bore; 4-59/64" Base to Center Height; V Lock Mount; Spherical |
| UNSPSC                    | 31171511  |

|                               |                              |
|-------------------------------|------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                |
| Noun                          | Bearing                      |
| Keyword String                | Pillow Block                 |
| Weight / LBS                  | 69                           |
| Bolt Spacing Maximum          | 14.409 Inch   366Millimeter  |
| Nominal Bolt Center to Center | 13.5 Inch   342.5 Millimeter |
| d                             | 3.75 Inch   95.25 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter         |
| Bolt Spacing Minimum          | 12.559 Inch   319Millimeter  |
| B                             | 4.921 Inch   125 Millimeter  |
| D                             | 4.134 Inch   105 Millimeter  |