

ISB NNU 41/530 K30M/W33 cylindrical roller bearings

ISB NNU 41/530 K30M/W33 cylindrical roller bearings, Units and Housings CAD models , Manufacturing Service 50x90x20 Size (mm) . Get 50 Bore Diameter (mm) Your Free.

Size (mm)	50x90x20
Bore Diameter (mm)	50
Outer Diameter (mm)	90
Width (mm)	20
d	50 mm
D	90 mm
B	20 mm
C	20 mm
r min.	1,1 mm
da min.	56,5 mm
da max	60 mm
Da max.	83,5 mm
ra max.	1 mm
Weight	0,459 Kg
Basic dynamic load rating (C)	35 kN
Basic static load rating (C0)	23,2 kN
(Grease) Lubrication Speed	7 100 r/min
Inventory	2.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.465
EAN	0029176015069

Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6210ZZ
Weight / LBS	0.481
Bore	1.969 Inch 50 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
bore diameter:	50 mm
snap ring included:	Without Snap Ring
outside diameter:	90 mm
internal clearance:	C0
overall width:	20 mm
dynamic load capacity:	35000 N
bore type:	Round

precision rating:	ABEC1, P0
closure type:	Double Shielded
finish/coating:	Uncoated
row type & fill slot:	Single Row Non-Fill Slot
cage material:	Steel Cage
SRI	6.57
hidYobi	6210ZZ
LangID	1
D_	90
SREX	0.025
B_	20
da min	56.5
hidTable	ecat_NSRDGB
SRE	6.57
mass	0.459
GRS rpm	7100
ra	1
SRIX	0.025
D_a	83.5
SRIN	-0.025
C0	23.2
fo	14.4
SREN	-0.025
DE_	82.7
Prod_Type3	DGBB_SR_ZZ
DA_	12.7
bomp	0
Z_	10
yobi	6210ZZ

C_conv	35000
ALPHA_	0
SDM_	70
r	1.1
KBRG	6141
SBRG	2
DI_	57.3