ISB NNU 4880 W33 cylindrical roller bearings

With over 10170 full-service stores, our ISB NNU 4880 W33 cylindrical roller bearings 25.4 mm B inventory is extensive and our 66.68 mm d parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

| d | 66.68 mm |
|------------------------------------|-----------|
| D | 107.95 mm |
| В | 25.4 mm |
| С | 19.05 mm |
| Т | 25.4 mm |
| d1 | 89 mm |
| a | 24.8 mm |
| e | 0.46 |
| Y2 | 1.31 |
| YO | 0.72 |
| Mass | 0.86 kg |
| Dynamic load, C | 91.5 kN |
| Rating life coefficient, A2 | 1.9 |
| Static load, CO | 140 kN |
| Fatigue limit load, Cu | 17.1 kN |
| Nlim (oil) | 4,300 rpm |
| Nlim (grease) | 3,200 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.45 Hz |

| Characteristic rolling element frequency, BSF | 9.95 Hz |
|---|----------|
| Characteristic outer ring frequency, BPF0 | 11.31 Hz |
| Characteristic inner ring frequency, BPFI | 13.69 Hz |
| ra max | 3.5 mm |
| rla max | 3.3 mm |