

# ISB NNU 4888 W33 cylindrical roller bearings

Online shopping ISB NNU 4888 W33 cylindrical roller bearings from 75x130x25 Size (mm) a great selection at Store. 130 Outer Diameter (mm) ... Accessories. 75 Bore Diameter (mm)

Size (mm)	75x130x25
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Width (mm)	25
d	75 mm
D	130 mm
B	25 mm
C	25 mm
rn	0,5 mm
r min.	1,5 mm
da min.	83 mm
da max	90,5 mm
Da max.	122 mm
ra max.	1,5 mm
Weight	1,18 Kg
Basic dynamic load rating (C)	66 kN
Basic static load rating (C0)	49,5 kN
(Grease) Lubrication Speed	4 800 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0

EAN	4547359005004
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   IS
Other Features	Deep Groove   Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	2.54
Bore	2.953 Inch   75 Millimeter
Outer Race Width	0.984 Inch   25 Millimeter
Outside Diameter	5.118 Inch   130 Millimeter
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	75 mm
precision rating:	ISO Class 0
outside diameter:	130 mm
finish/coating:	Uncoated

overall width:	25 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	25 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	25 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4800 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	5600 RPM
dynamic load capacity:	66000 N
series:	62
static load capacity:	49500 N
manufacturer product page:	<a href="#">Click here</a>