

# ISB NU 1013 cylindrical roller bearings

LET OUR ISB NU 1013 cylindrical roller bearings EXPERTS GET YOU THE PARTS YOU NEED. 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ASAHI BEARINGS   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 7.9  |
| EAN                       | 0808250328796  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Teflon Coated Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | UC215-47   |
| Seals                     | Contact Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   Normal Duty   Has Slinger   |
| Long Description          | 2 Bolt Pillow Block; 2-15/16" Bore; 3-1/4" Base to Center Height; Set Screw Mount; Ball Be |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Weight / LBS                  | 17.41                          |
| d                             | 2.938 Inch   74.625 Millimeter |
| Bolt Spacing Maximum          | 8.969 Inch   227.813Millimeter |
| B                             | 3.25 Inch   82.55 Millimeter   |
| D                             | 3.063 Inch   77.8 Millimeter   |
| Nominal Bolt Center to Center | 8.5 Inch   215.5 Millimeter    |
| Bolt Spacing Minimum          | 8.031 Inch   204Millimeter     |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |