

ISB NU 2256 cylindrical roller bearings

Advance ISB NU 2256 cylindrical roller bearings is your source for 145 Bore Diameter (mm) quality and accessories. shop online for home delivery or 95 Outer Diameter (mm) pick up in 145x95x24 Size (mm) one of our 10000 .

Size (mm)	145x95x24
Bore Diameter (mm)	145
Outer Diameter (mm)	95
Width (mm)	24
d	95 mm
D	145 mm
B	24 mm
d1	111.4 mm
D2	133.3 mm
r1,2 – min.	1.5 mm
da – min.	102 mm
da – max.	111 mm
Da – max.	138 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	63.7 kN
Basic static load rating – C0	54 kN
Fatigue load limit – Pu	2.1 kN
Reference speed	9500 r/min
Limiting speed	6000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	15.8

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.29
EAN	7316570313222
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	95MM Bore; 145MM Outside Diameter; 24MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6019-Z
Weight / LBS	2.83
Bore	3.74 Inch 95 Millimeter
Outside Diameter	5.709 Inch 145 Millimeter
Outer Race Width	0.945 Inch 24 Millimeter
d1 ≈	111.4 mm
D2 ≈	133.3 mm

r _{1,2} min.	1.5 mm
d _a min.	102 mm
d _a max.	111 mm
D _a max.	138 mm
r _a max.	1.5 mm
Basic dynamic load rating C	63.7 kN
Basic static load rating C ₀	54 kN
Fatigue load limit P _u	2.08 kN
Calculation factor k _r	0.025
Calculation factor f ₀	15.8
Mass bearing	1.26 kg