

ISB TSF.R 20 plain bearings

ISB TSF.R 20 plain bearings 19x7x6 Size (mm) Engineering Calculator , Manufacturing Service . Get Your Free.

Size (mm)	19x7x6
Bore Diameter (mm)	19
Outer Diameter (mm)	7
Width (mm)	6
d	7 mm
D	19 mm
B	6 mm
d1	10.8 mm
d2	10.8 mm
D1	15.2 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.15 mm
a	4.8 mm
da – min.	9 mm
db – min.	9 mm
Da – max.	17 mm
Db – max.	18.2 mm
ra – max.	0.3 mm
rb – max.	0.15 mm
dn	11.7 mm
Basic dynamic load rating – C	2.5 kN
Basic static load rating – C0	0.98 kN
Fatigue load limit – Pu	0.04 kN
Limiting speed for grease lubrication	100000 r/min

Limiting speed for oil lubrication	160000 mm/min
Ball – Dw	3.572 mm
Ball – z	8
Gref	0.12 cm ³
Calculation factor – f ₀	8.1
Preload class A – GA	8 N
Preload class B – GB	15 N
Preload class C – GC	30 N
Preload class D – GD	60 N
Calculation factor – f	1
Calculation factor – f _{2A}	1
Calculation factor – f _{2B}	1.02
Calculation factor – f _{2C}	1.05
Calculation factor – f _{2D}	1.09
Calculation factor – f _{HC}	1
Preload class A	9 N/micron
Preload class B	11 N/micron
Preload class C	15 N/micron
Preload class D	22 N/micron
r _{1,2} min.	0.3 mm
r _{3,4} min.	0.15 mm
d _a min.	9 mm
d _b min.	9 mm
D _a max.	17 mm
D _b max.	18.2 mm
r _a max.	0.3 mm
r _b max.	0.15 mm
Basic dynamic load rating C	2.51 kN
Basic static load rating C ₀	0.98 kN

Fatigue load limit P_u	0.04 kN
Attainable speed for grease lubrication	100000 r/min
Attainable speed for oil-air lubrication	160000 r/min
Ball diameter D_w	3.572 mm
Number of balls z	8
Reference grease quantity G_{ref}	0.12 cm ³
Preload class A G_A	8 N
Static axial stiffness, preload class A	9 N/ μ m
Preload class B G_B	15 N
Static axial stiffness, preload class B	11 N/ μ m
Preload class C G_C	30 N
Static axial stiffness, preload class C	15 N/ μ m
Preload class D G_D	60 N
Static axial stiffness, preload class D	22 N/ μ m
Calculation factor f	1.03
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.09
Calculation factor f_{HC}	1
Calculation factor f_{θ}	8.1
Mass bearing	0.008 kg