

ISB TSM 12.1 plain bearings

LET OUR 57.785 mm Ca ISB TSM 12.1 plain bearings EXPERTS GET YOU 140 mm Da THE 55.563 mm da PARTS YOU NEED.

da	55.563 mm
Da	140 mm
Ca	57.785 mm
A1	88.9 mm
A2	209.55 mm
S	4.763 mm
ba	40.481 mm
H	167.481 mm
H1	88.9 mm
H2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	46.038 mm
R2	21.431 mm
RG	3/8 NPT
PG	1/8 NPT
h	35.719 mm
Housing	FSAF 613
Bearing	22313 EK
Adapter sleeve assembly	SNW 113×2.3/16
Stabilizing ring	SR-16-13

Taconite seal	TER 32
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1400 r/min
P60°	60.5 kN
P90°	36 kN
P120°	21.8 kN
P150°	19.6 kN
P180°	23.1 kN
Pa	9.43 kN
Mass pillow block	18.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g