

ISB YRT 950 thrust roller bearings

With over 10170 full-service stores, our ISB YRT 950 thrust roller bearings inventory is extensive and our parts are 290 Bore Diameter (mm) priced right. 290x200x140 Size (mm) within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

| | |
|---------------------|-------------|
| Size (mm) | 290x200x140 |
| Bore Diameter (mm) | 290 |
| Outer Diameter (mm) | 200 |
| Width (mm) | 140 |
| d | 200 mm |
| D | 290 mm |
| B | 140 mm |
| C | 134 mm |
| α | 2 ° |
| dk | 260 mm |
| b | 11.5 mm |
| b1 | 11.5 mm |
| M | 5 mm |
| r1 – min. | 1.1 mm |
| r2 – min. | 1.1 mm |
| da – min. | 211 mm |
| da – max. | 219 mm |
| Da – min. | 242 mm |
| Da – max. | 276 mm |
| ra – max. | 1 mm |

| | |
|----------------------------------|---|
| rb – max. | 1 mm |
| Basic dynamic load rating – C | 2450 kN |
| Basic static load rating – C0 | 3650 kN |
| Specific factor dynamic load – K | 80 N/mm2 |
| Specific factor static load – K0 | 120 N/mm2 |
| Constant – KM | 1055 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 39 |
| EAN | 7316570445831 |
| Product Group | B04264 |
| Self Aligning | Yes |
| Rolling Element | Spherical Plain |
| Material – Outer Member | Steel |
| Material – Ball | Steel |
| Material – Liner | Plastic Teflon |
| Relubricatable | Yes |
| Enclosure | Open |
| Other Features | 3 Piece Radially Split Outer Ring Chrome Plated Ball Separable Self Lubricating Lubricatio |
| Long Description | 200MM Bore; 134MM Housing Width; 290MM Outside Diameter; Spherical Plain; Steel Outer Member; Steel |
| Inch – Metric | Metric |
| UNSPSC | 31171515 |
| Harmonized Tariff Code | 8483.30.80.70 |

| | |
|--|------------------------------------|
| Noun | Bearing |
| Keyword 3 | Spherical |
| Keyword String | Plain Spherical Radial |
| Manufacturer Item Number | GEP 200 FS |
| Weight / LBS | 73.855 |
| Housing Width | 5.276 Inch 134 Millimeter |
| Outside Diameter | 11.417 Inch 290 Millimeter |
| Overall Width | 5.512 Inch 140 Millimeter |
| Bore | 7.874 Inch 200 Millimeter |
| Lubricant | Maintenance free – dry lubrication |
| Design (sliding contact surface combination) | Steel/PTFE FRP |
| Sealing solution | – |
| α | 2 ° |
| r1 min. | 1.1 mm |
| r2 min. | 1.1 mm |
| da min. | 211 mm |
| da max. | 219 mm |
| Da min. | 242 mm |
| Da max. | 276 mm |
| ra max. | 1 mm |
| rb max. | 1 mm |
| Basic dynamic load rating C | 2450 kN |
| Basic static load rating C0 | 3650 kN |
| Specific dynamic load factor K | 80 N/mm ² |
| Specific static load factor K0 | 120 N/mm ² |
| Material constant KM | 1055 |
| Mass plain bearing | 33.5 kg |