

# ISO 1216K+H216 self aligning ball bearings

170 Million used ISO 1216K+H216 self aligning ball bearings instantly searchable. Shop our large 1769 lb radial static load capacity: selection of parts based on brand, price, description, and location. Order the 25 mm d with 41.4 mm D stock ...

|                               |  |
|-------------------------------|--|
| d                             | 25 mm  |
| radial static load capacity:  | 1769 lb                                      |
| D                             | 41.4 mm                                      |
| seal type:                    | Triple Lip with Flinger                      |
| B                             | 68.8 mm                                      |
| length through bore:          | 40.6 mm                                      |
| bore type:                    | Round  |
| finish/coating:               | Uncoated                                     |
| duty type:                    | Standard Duty                                |
| maximum rpm:                  | 6000 RPM                                     |
| mounting type:                | Three-Bolt Bracket Style                     |
| lubrication type:             | Lubrication Fitting                          |
| housing material:             | Polymer                                      |
| series:                       | 205  |
| locking device:               | Concentric Collar                            |
| standards met:                | UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA |
| expansion type:               | Non-Expansion Bearing (Fixed)                |
| manufacturer catalog number:  | 127649                                       |
| radial dynamic load capacity: | 3146 lb                                      |