

# ISO 2316 self aligning ball bearings

ISO 2316 self aligning ball bearings N/A Minimum Buy Quantity Industries and Applications ? We sell discount online as well as cheap 0.0 Inventory machinery parts.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 3.904   |
| EAN                       | 0698210639334   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Round Flange Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 2111U   |
| Seals                     | Light Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Block;<br>1-11/16" Bore; 5-1/2" Bolt<br>Circle; 3-57/64" Bolt<br>Spacing; |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Collar   With Set Screw |
| UNSPSC                             | 31171501                                    |
| Harmonized Tariff Code             | 8483.20.40.80                               |
| Noun                               | Bearing                                     |
| Keyword String                     | Flanged                                     |
| Manufacturer Item Number           | KB2111                                      |
| Manufacturer Internal Number       | 6863933                                     |
| Weight / LBS                       | 8.6   |
| D                                  | 3.125 Inch   79.38 Millimeter               |
| Nominal Bolt Circle Diameter Round | 5.5 Inch   140 Millimeter                   |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                       |
| d                                  | 1.688 Inch   42.875 Millimeter              |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                       |
| Bolt Spacing                       | 3.891 Inch   98.83 Millimeter               |