

ISO 239/1180 KW33 spherical roller bearings

With over 10170 full-service stores, our ISO 239/1180 KW33 spherical roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your 0.0 Inventory productivity by saving time and your hard-earned dollars.

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0
EAN	0692314504970
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-2317
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allow High Misalignment 2 To 4 Deg
Long Description	85MM Bore; Tapered Adapter Mount; 180MM Outside Diameter; 60MM Inner Race Width; 60MM Outer Race Wid
Inch – Metric	Metric

UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Manufacturer Item Number	2317K
Weight / LBS	14.46232
Inner Race Width	2.362 Inch 60 Millimeter
Outer Race Width	2.362 Inch 60 Millimeter
d	3.346 Inch 85 Millimeter
D	7.087 Inch 180 Millimeter
bore diameter:	85 mm
precision rating:	Class 0
outside diameter:	180 mm
maximum rpm:	3800 rpm
overall width:	60 mm
bearing material:	High Carbon Chrome Steel
bore type:	Tapered 1:12
cage material:	Steel
closure type:	Open
finish/coating:	Uncoated
internal clearance:	CN
outer ring width:	60 mm
operating temperature range:	-40 to 120 °C
fillet radius:	3 mm
dynamic load capacity:	142000 N
manufacturer product page:	Click here
static load capacity:	51500 N