

ISO 23930 KW33 spherical roller bearings

Welcome to the ISO 23930 KW33 spherical roller bearings 130 Outer Diameter (mm) online seller. 85x130x14 Size (mm)

Size (mm)	85x130x14
Bore Diameter (mm)	85
Outer Diameter (mm)	130
Width (mm)	14
d	85 mm
D	130 mm
B	14 mm
C	14 mm
r min.	0,6 mm
da min.	89 mm
Da max.	126 mm
ra max.	0,6 mm
Weight	0,652 Kg
Basic dynamic load rating (C)	33 kN
Basic static load rating (C0)	31,5 kN
(Grease) Lubrication Speed	5 000 r/min
(Oil) Lubrication Speed	6 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.65
EAN	0029176059506
Product Group	B00308

Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	85MM Bore; 130MM Outside Diameter; 14MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.433
Outer Race Width	0.551 Inch 14 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Bore	3.346 Inch 85 Millimeter
bore diameter:	85 mm
closure type:	Open
outside diameter:	130 mm
internal clearance:	Normal Clearance
overall width:	14 mm
manufacturer upc number:	029176059506
bore type:	Round
SRI	5.34
hidYobi	16017

LangID	1
D_	130
SREX	0.025
B_	14
da min	89
hidTable	ecat_NSRDGB
Oil rpm	6000
SRE	5.34
mass	0.652
GRS rpm	5000
ra	0.6
SRIX	0.025
D_a	126
SRIN	-0.025
C0	31.5
fo	16.5
SREN	-0.025
DE_	117.819
Prod_Type3	DGBB_SR_OT
DA_	10.319
bomp	0
Z_	18
yobi	16017
C_conv	33000
ALPHA_	0
SDM_	107.5
r	0.6
KBRG	6101
SBRG	0

DI_	97.181
-----	--------