

# ISO 6008 ZZ deep groove ball bearings

Can't find what you're looking for ISO 6008 ZZ deep groove ball bearings ? Our expert 260 mm D Representatives be 120 mm d in contact with 55 mm B you shortly!

d	120 mm
D	260 mm
B	55 mm
E	226 mm
F	154 mm
rs min	3 mm
r1s min	3 mm
Radial clearance class	C3
Mass (without HJ ring)	15.4 kg
Dynamic load, C	450 kN
Static load, C0	510 kN
Fatigue limit load, Cu	51.3 kN
Nlim (oil)	3,200 rpm
Nlim (grease)	2,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	133 mm
da max	151 mm
db min	156 mm
Da max	247 mm
ra max	2.5 mm
r1a max	2.5 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	14.15
EAN	4547359147926
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	120MM Bore; Straight Bore Profile; 260MM Outside Diameter; 55MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU324G1C3

Weight / LBS	31.161
Outside Diameter	10.236 Inch   260 Millimeter
Bore	4.724 Inch   120 Millimeter
Width	2.165 Inch   55 Millimeter
bore diameter:	120 mm
static load capacity:	510000 N
outside diameter:	260 mm
precision rating:	ISO Class 0
overall width:	55 mm
maximum rpm:	3200 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	2.5 mm
operating temperature range:	-40 to 120 °C
manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	450000 N