## ISO 6020 ZZ deep groove ball bearings

What are the types of ISO 6020 ZZ deep groove ball bearings ? Manufacturing Service . Get Your Free, Instant price, 0.0 Inventory design review.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.17  |
| EAN                       | 0662288481874  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Tapered Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | RCI-204-C  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 2 Piece Split  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Heavy Duty   Double<br>Collar   Has Flinger   With Set<br>Screw |

| Long Description                 | 4 Bolt Pillow Block; 2-1/4" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; T |
|----------------------------------|--|
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.80  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer Item Number         | RPB 204-C4   |
| Manufacturer Internal Number     | 551268   |
| Weight / LBS                     | 22.4   |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter   |
| d                                | 2.25 Inch   57.15 Millimeter   |
| D                                | 4 Inch   101.6 Millimeter  |
| Bolt Spacing Maximum             | 8.75 Inch   222.25Millimeter   |
| В                                | 2.75 Inch   69.85 Millimeter   |
| Nominal Bolt Center to<br>Center | 8.3 Inch   210 Millimeter  |
| Bolt Spacing Minimum             | 7.75 Inch   196.85Millimeter   |