

ISO 61808 ZZ deep groove ball bearings

High Quality ISO 61808 ZZ deep groove ball bearings. Competitive 6 RoHS Pricing. Accept [Steel] Steel Inner/Outer Ring Material Small Order. Quote Days to Ship Easy and Fast Shipping.

| | |
|-------------------------------------|-----------------------------|
| Days to Ship | Quote |
| RoHS | 6 |
| Inner/Outer Ring Material | [Steel] Steel |
| Bearing Style | Open Type |
| Outer Ring Shape | With Retaining Ring Grooves |
| Precision | Grade 0 |
| I.D.(Ø) | 35 |
| O.D.(Ø) | 62 |
| Width(mm) | 14 |
| Basic Dynamic Load Rating(N) | 16000 |
| Max. Allowed rpm(rpm) | 11000 |
| Rolling Element Material | [Steel] Steel |
| Retainer Type | Punching |
| Basic Load Rating, Static Rating(N) | 10300 |
| Clearance sign | CN (standard) |
| Accuracy(Class) | Class 0 |
| Acoustic Symbol | No |
| Holder Symbol | No |
| Symbol of Bearing Ring Shape | NR |
| Seal, Shield Symbols | No |

| | |
|-----------------------------|-----------------|
| Precision Grade Symbol | No |
| Special Configurations Code | No |
| Rubugado Symbol | No |
| Material Symbol | No |
| Spacer, Sleeve symbol | No |
| Types | No |
| Type | Ball |
| Specifications, Environment | Standard |
| Load Direction | Radial |
| Outer Ring | With Outer Ring |
| Number of Raceway Ring Rows | Single Row |
| Size Standards | Metric System |
| Combination symbol | No |
| Low Torque Specification | No |
| Internal Symbol | No |
| Torque Symbol | No |
| d | 35 |
| D | 62 |
| B | 14 |
| Specifications/Environment | Standard |