

ISO 7018 BDB angular contact ball bearings

Shop ISO 7018 BDB angular contact ball bearings huge online discount 72 Bore Diameter (mm) inventory. and Import machinery parts your car needs with Free 72x60x40 Size (mm) Shipping and Free Extended Warranty.

Size (mm)	72x60x40
Bore Diameter (mm)	72
Outer Diameter (mm)	60
Width (mm)	40
Fw	60 mm
D	72 mm
C	40 mm
C1	17 mm
C2	12 mm
d	60 mm
D2	86.5 mm
r _{1,2} – min.	1 mm
da – min.	80.5 mm
ra – max.	1 mm
rb – max.	1 mm
d _i	50 mm
F	60 mm
B _i	25 mm
Basic dynamic load rating, radial direction – C	41.8 kN
Basic static load rating, radial direction – C0	96.5 kN

Basic dynamic load rating, axial direction – C	41.6 kN
Basic static load rating, axial direction – C0	122 kN
Fatigue load limit, radial direction – Pu	11.8 kN
Fatigue load limit, axial direction – Pu	4.6 kN
Reference speed	3600 r/min
Limiting speed	3000 r/min
Mass bearing	0.38 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.495
EAN	7316570240337
Product Group	B04144
bore diameter:	60 mm
bearing material:	Steel
outside diameter:	72 mm
maximum rpm:	3600 rpm
overall width:	40 mm
cage material:	Steel
bearing type:	Needle Roller/Axial Ball Bearing
series:	AXK
radial dynamic load capacity:	41.8 kN
manufacturer product page:	Click here
radial static load capacity:	96.5 kN
manufacturer upc number:	7316570240337

r _{1,2} min.	1 mm
d _a min.	80.5 mm
r _a max.	1 mm
r _b max.	1 mm
Basic dynamic load rating, radial direction C	41.8 kN
Basic static load rating, radial direction C ₀	96.5 kN
Basic dynamic load rating, axial direction C	41.6 kN
Basic static load rating, axial direction C ₀	122 kN
Fatigue load limit, radial direction P _u	11.8 kN
Fatigue load limit, axial direction P _u	4.55 kN
Minimum axial load factor A	0.077
Inner ring	IR 50x60x25