

ISO 7019 BDF angular contact ball bearings

Various types and 75 Bore Diameter (mm) sizes to accommodate your 75x130x25 Size (mm) ISO 7019 BDF angular contact ball bearings 130 Outer Diameter (mm) requirements.

Size (mm)	75x130x25
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Width (mm)	25
d	75 mm
D	130 mm
B	25 mm
C	25 mm
Angle (α)	40 °
a	30.6 mm
r min.	1.5 mm
r1 min.	1 mm
da min.	84 mm
Da max.	121 mm
ra max.	1.5 mm
Weight	1.23 Kg
Basic dynamic load rating (C)	74 kN
Basic static load rating (C0)	64 kN
(Grease) Lubrication Speed	4000 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A

Weight / Kilogram	1.23
EAN	4991893844740
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7215 B BNLS
Weight / LBS	2.71
Bore	2.953 Inch 75 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Width	0.984 Inch 25 Millimeter
Configuration	Single Row
Bore Type	Cylindrical Bore

Bore Size	75 mm
Fillet Radius/Chamfer	1.5 mm
r1	1 mm
Dynamic Load Rating	74,000 N
Static Load Rating	64,000 N
Limiting Speed – Grease	4,000 rpm
Limiting Speed – Oil	5,300 rpm
da1 (min)	84 mm
da2 (min)	80 mm
Da1 (max)	121 mm
Da2 (max)	124.6 mm
ra (max)	1.5 mm
ra1 (max)	1 mm