

ISO 71910 CDT angular contact ball bearings

Online shopping ISO 71910 CDT angular contact ball bearings from a great selection at Store. ... 130 mm da Accessories. 149.225 mm db

| | |
|--------|------------|
| da | 130 mm |
| db | 149.225 mm |
| dc | 125.412 mm |
| Da | 279.999 mm |
| Ca | 102.794 mm |
| A1 | 158.75 mm |
| A2 | 288.925 mm |
| S | 4.763 mm |
| ba | 72.231 mm |
| H | 336.55 mm |
| H1 | 169.875 mm |
| H2 | 66.675 mm |
| J min. | 441.325 mm |
| J max. | 488.95 mm |
| J1 | 95.25 mm |
| L | 558.8 mm |
| N1 | 28.575 mm |
| R1 | 104.775 mm |
| R2 | 33.337 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 61.913 mm |

| | |
|--|----------------|
| Housing | SAF 326 |
| Bearing | 22326 CC/W33 |
| Lock nut | AN 26 |
| Lock washer | W 26 |
| Stabilizing ring | SR-0-26 |
| Taconite seal (db shaft position) | TER 136 |
| Taconite seal (dc shaft position) | TER 122 |
| End plug (suffix Y) | EPR 27 |
| Max. speed for Taconite seal | 520 r/min |
| P60° | 226 kN |
| P90° | 136 kN |
| P120° | 85.9 kN |
| P150° | 78.3 kN |
| P180° | 94.3 kN |
| Pa | 60.9 kN |
| Mass pillow block | 100 kg |
| Cap bolt | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 203.4 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 1 in |
| Initial grease fill | 793.8 g |