

# ISO 7228 BDF angular contact ball bearings

offers a ISO 7228 BDF angular contact ball bearings selection of Genuine at Wholesale Prices. We TIMKEN Manufacturer Name are a ISO 7228 BDF angular contact ball bearings N/A Minimum Buy Quantity Certified Parts 0.0 Inventory Retailer

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.442   |
| EAN                       | 0883450045070                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 3/4 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Triple Lip Viton                               |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Collar  <br>With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 75MM Bore;<br>79.4MM Base to Center Height;<br>Concentric Collar Mount;<br>Spherical Rol |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QAP15A075SN   |
| Weight / LBS                  | 28  |
| D                             | 3.62 Inch   91.948 Millimeter   |
| Bolt Spacing Maximum          | 9.625 Inch   244.475Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| Nominal Bolt Center to Center | 8.8 Inch   223 Millimeter   |
| d                             | 2.953 Inch   75 Millimeter  |
| Bolt Spacing Minimum          | 7.875 Inch   200.025Millimeter  |
| B                             | 3.126 Inch   79.4 Millimeter  |