

# ISO 7240 BDF angular contact ball bearings

Online ISO 7240 BDF angular contact ball bearings 3.0 Inventory Expert. More Choices. ISO 7240 BDF angular contact ball bearings in N/A Minimum Buy Quantity Stock & Ready to Ship Now!

|                           |  |
|---------------------------|--|
| Inventory                 | 3.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 5.584  |
| EAN                       | 0662461031889  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                    |
| Housing Style             | 2 Bolt Pillow Block                                  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 3-115T   |
| Seals                     | Felt Labyrinth                                       |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Medium Duty  <br>Skwezloc   Has Flinger |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-15/16" Bore; 2-1/2" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | MP-31T   |
| Manufacturer Internal Number  | 705655   |
| Weight / LBS                  | 12.3   |
| Bolt Spacing Maximum          | 7.563 Inch   192.1Millimeter   |
| B                             | 2.5 Inch   63.5 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 2.188 Inch   55.575 Millimeter   |
| Nominal Bolt Center to Center | 6.8 Inch   171.5 Millimeter  |
| Bolt Spacing Minimum          | 5.938 Inch   150.825Millimeter   |
| d                             | 1.938 Inch   49.225 Millimeter   |