

# ISO 7302 ADT angular contact ball bearings

offers a ISO 7302 ADT angular contact ball bearings selection of Genuine 60 Bore Diameter (mm) at Wholesale Prices. We are a ISO 7302 ADT angular contact ball bearings Certified Parts 60x110x22 Size (mm) Retailer

Size (mm)	60x110x22
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Width (mm)	22
d	60 mm
D	110 mm
B	22 mm
C	22 mm
r min.	1,5 mm
da min.	68 mm
da max	75 mm
Da max.	102 mm
ra max.	1,5 mm
Weight	0,783 Kg
Basic dynamic load rating (C)	52,5 kN
Basic static load rating (C0)	36 kN
(Grease) Lubrication Speed	6 000 r/min
(Oil) Lubrication Speed	7 000 r/min
rs min	1.5 mm
Radial clearance class	CN
Mass	0.78 kg

Dynamic load, C	52.5 kN
Static load, C0	36 kN
Fatigue limit load, Cu	1.64 kN
f0	14.3
Nlim (oil)	7,000 rpm
Nlim (grease)	6,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.26 Hz
Characteristic outer ring frequency, BPF0	4.08 Hz
Characteristic inner ring frequency, BRFI	5.92 Hz
da min	68 mm
Da max	102 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.766
EAN	4547359004854
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No

Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fi
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6212
Weight / LBS	1.73
Bore	2.362 Inch   60 Millimeter
Outside Diameter	4.331 Inch   110 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.866 Inch   22 Millimeter
bore diameter:	60 mm
finish/coating:	Uncoated
outside diameter:	110 mm
bearing material:	High Carbon Chrome Steel
overall width:	22 mm
cage material:	Steel
bore type:	Round
inner ring width:	22 mm

closure type:	Open
outer ring width:	22 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	6000 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	7000 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	7000 RPM
dynamic load capacity:	52500 N
series:	62
static load capacity:	36000 N
manufacturer product page:	<a href="#">Click here</a>
precision rating:	Class 0