

# ISO 7413 B angular contact ball bearings

ISO 7413 B angular contact ball bearings 17 mm D 9 mm d with easy-to-use parts graphics, giving you the ability to check parts availability, 5 mm B pricing, examine remanufactured options.

d	9 mm
D	17 mm
B	5 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	3.2 kg
Dynamic load, C	1.72 kN
Static load, C0	0.82 kN
Fatigue limit load, Cu	0.04 kN
f0	14.4
Nlim (oil)	39,000 rpm
Nlim (grease)	33,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	15.5 mm
Da max	10.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0.004
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	9MM Bore; 17MM Outside Diameter; 5MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P
Other Features	Deep Groove   Miniature Bearing   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Outside Diameter	0.669 Inch   17 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.197 Inch   5 Millimeter
Bore	0.354 Inch   9 Millimeter