

ISO 81220 thrust roller bearings

We Provide Extensive ISO 81220 thrust roller bearings Selection And Competitive 122.237 mm da 111.785 mm Ca Wholesale Pricing.

da	122.237 mm
Da	299.999 mm
Ca	111.785 mm
A1	171.45 mm
A2	307.975 mm
S	4.763 mm
ba	78.581 mm
H	360.363 mm
H1	179.375 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	65.088 mm
Housing	SAF 628
Bearing	22328 CCK/W33

Adapter sleeve assembly	SNW 128×4.13/16
Stabilizing ring	SR-0-28
Taconite seal	TER 120
End plug (suffix Y)	EPR 27
Max. speed for Taconite seal	625 r/min
P60°	234 kN
P90°	140 kN
P120°	85.9 kN
P150°	77 kN
P180°	92.5 kN
Pa	42.9 kN
Mass pillow block	134 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g