

ISO BK121816 cylindrical roller bearings

We Provide Extensive ISO BK121816 cylindrical roller bearings N/A Minimum Buy Quantity Selection 0.0 Inventory And Competitive Wholesale Pricing.

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 1.8 |
| EAN | 0029176015687 |
| Product Group | B00308 |
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C3-Loose |
| Inch – Metric | Metric |
| Long Description | 85MM Bore; 150MM Outside Diameter; 28MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |

| | |
|------------------------------|-----------------------------|
| Manufacturer Item Number | 6217ZZC3 |
| Weight / LBS | 1.756 |
| Outer Race Width | 1.102 Inch 28 Millimeter |
| D | 5.906 Inch 150 Millimeter |
| d | 3.346 Inch 85 Millimeter |
| bore diameter: | 85 mm |
| static load capacity: | 62000 N |
| outside diameter: | 150 mm |
| precision rating: | ABEC 1 (ISO Class Normal) |
| overall width: | 28 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Double Shielded |
| outer ring width: | 28 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| fillet radius: | 2 mm |
| internal clearance: | C3 |
| maximum rpm: | 5000 RPM |
| operating temperature range: | -10 to +110 °C |
| series: | 62 |
| dynamic load capacity: | 84000 N |