

# ISO BK142216 cylindrical roller bearings

Find 0.0 Inventory the discount ISO BK142216 cylindrical roller bearings online you need . We offer ... If you check out our large selection of ISO BK142216 cylindrical roller bearings once .

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.72  |
| EAN                       | 0793699530872   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | B22440EL  |
| Seals                     | Spring Loaded Lip   |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Single Collar  <br>Extended Inner Race   With Set<br>Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2-1/2" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; S |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | EPEB22440E   |
| Manufacturer Internal Number  | 0153087  |
| Weight / LBS                  | 17   |
| Bolt Spacing Minimum          | 6.938 Inch   176.225Millimeter   |
| Nominal Bolt Center to Center | 7.8 Inch   199.2 Millimeter  |
| Bolt Spacing Maximum          | 8.75 Inch   222.25Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| B                             | 2.75 Inch   69.85 Millimeter   |
| D                             | 3.5 Inch   88.9 Millimeter   |
| d                             | 2.5 Inch   63.5 Millimeter   |