

# ISO BK3014 cylindrical roller bearings

High Quality ISO BK3014 cylindrical roller bearings. Competitive 26 Outer Diameter (mm) Pricing. Accept Small 9x26x8 Size (mm) Order. 9 Bore Diameter (mm) Easy and Fast Shipping.

|                               |         |
|-------------------------------|---------|
| Size (mm)                     | 9x26x8  |
| Bore Diameter (mm)            | 9       |
| Outer Diameter (mm)           | 26      |
| Width (mm)                    | 8       |
| d                             | 9 mm    |
| D                             | 26 mm   |
| B                             | 8 mm    |
| C                             | 8 mm    |
| d1                            | – mm    |
| d2                            | 13 mm   |
| r1 min.                       | 11,4 mm |
| r2 min.                       | 11,4 mm |
| D1                            | 22,6 mm |
| D2                            | 0,3 mm  |
| da min.                       | 11.4 mm |
| Da max.                       | 23.6 mm |
| ra max.                       | 0.3 mm  |
| Weight                        | 0,02 Kg |
| Basic dynamic load rating (C) | 4,75 kN |
| Basic static load rating (C0) | 1,96 kN |
| Fatigue load limit (Pu)       | 0,083   |

|                                 |  |
|---------------------------------|--|
| Reference speed                 | 60000 r/min  |
| Limiting speed                  | 30000 r/min  |
| Calculation factor (f0)         | 12   |
| Inventory                       | 0.0  |
| Manufacturer Name               | SKF  |
| Minimum Buy Quantity            | N/A  |
| Weight / Kilogram               | 0.019  |
| EAN                             | 7316571840130  |
| Product Group                   | B00308   |
| Enclosure                       | 2 Seals  |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Rolling Element                 | Ball Bearing   |
| Snap Ring                       | No   |
| Internal Special Features       | No   |
| Cage Material                   | Steel  |
| Enclosure Type                  | Contact Seal   |
| Internal Clearance              | C0-Medium  |
| Inch – Metric                   | Metric   |
| Long Description                | 9MM Bore; 26MM Outside Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Fi |
| Other Features                  | Deep Groove   Low Friction   NBR Seal  |
| UNSPSC                          | 31171504   |
| Harmonized Tariff Code          | 8482.10.50.68  |
| Noun                            | Bearing  |
| Keyword String                  | Ball   |
| Weight / LBS                    | 0.02   |

|                             |                            |
|-----------------------------|----------------------------|
| Outside Diameter            | 1.024 Inch   26 Millimeter |
| Outer Race Width            | 0.315 Inch   8 Millimeter  |
| Bore                        | 0.354 Inch   9 Millimeter  |
| Inner Race Width            | 0 Inch   0 Millimeter      |
| d2 ≈                        | 12.55 mm                   |
| D2 ≈                        | 22.6 mm                    |
| r1,2 min.                   | 0.3 mm                     |
| da max.                     | 12.5 mm                    |
| Basic dynamic load rating C | 4.75 kN                    |
| Basic static load rating C0 | 1.96 kN                    |
| Fatigue load limit Pu       | 0.083 kN                   |
| Calculation factor kr       | 0.025                      |
| Calculation factor f0       | 12                         |
| Mass bearing                | 0.02 kg                    |