

ISO BK6024 cylindrical roller bearings

High 380 mm d Quality ISO BK6024 cylindrical roller bearings. Competitive Pricing. Accept 240 mm B Small Order. Easy and 680 mm D Fast Shipping.

d	380 mm
D	680 mm
B	240 mm
d2	476 mm
D1	574.4 mm
rs min	6 mm
Number of lubrication holes	8
b	33 mm
k	20 mm
Associated sleeve reference	H3276
e	0.36
Y1	1.89
Y2	2.82
Y0	1.85
Radial clearance class	CN
Dynamic load, C	5,200 kN
Static load, C0	9,650 kN
Fatigue limit load, Cu	581 kN
Nref	400 rpm
Nlim	800 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.28 Hz
Characteristic outer ring frequency, BPF0	8.69 Hz
Characteristic inner ring frequency, BRFI	11.31 Hz
da min	406 mm
db min	405 mm
Ce min	15 mm
Da max	654 mm
ra max	5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359286915
Product Group	B04311