ISO GE20DO plain bearings

are a few brands you will find in our inventory. Find ISO GE20D0 plain bearings to 1.5000 in d see what's in stock!

d1.5000 inradial static load capacity:4467 lbD4.0000 inseal type:Single Lip ContactB2.1094 inlength through bore:1.7656 inbore type:Roundmaximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Lubrication Fitting
D4.0000 inseal type:Single Lip ContactB2.1094 inlength through bore:1.7656 inbore type:Roundmaximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
seal type:Single Lip ContactB2.1094 inlength through bore:1.7656 inbore type:Roundmaximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
B2.1094 inlength through bore:1.7656 inbore type:Roundmaximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:u
length through bore:1.7656 inbore type:Roundmaximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
bore type: Round maximum operating temperature: 200 °F duty type: Intermediate Duty finish/coating: Gray Painted mounting type: Four-Bolt Flange bolt size: 0.5000 in housing material: Cast Iron maximum rpm: 2500 RPM
maximum operating temperature:200 °Fduty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
duty type:Intermediate Dutyfinish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
finish/coating:Gray Paintedmounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
mounting type:Four-Bolt Flangebolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
bolt size:0.5000 inhousing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
housing material:Cast Ironmaximum rpm:2500 RPMlocking device:Eccentric Collar
maximum rpm: 2500 RPM locking device: Eccentric Collar
locking device: Eccentric Collar
lubrication type:
expansion type: Non-Expansion Bearing (Fixed)
series: VF4E 100
housing width: 0.6250 in
application: Browning — Standard
replacement bearing: VE-124
inner ring width: 1.7656 in
manufacturer catalog number: 767320
bearing material: 52100 Bearing Steel

manufacturer product page:	Click here
radial dynamic load capacity:	7340 lb