

# ISO HK0912 cylindrical roller bearings

ISO HK0912 cylindrical roller bearings SEARCH TIMKEN  
Manufacturer Name – Whether it's agriculture or construction equipment your working on, Has N/A Minimum Buy Quantity the 0.0 Inventory you need.

|                           |                            |
|---------------------------|----------------------------|
| Inventory                 | 0.0                        |
| Manufacturer Name         | TIMKEN                     |
| Minimum Buy Quantity      | N/A                        |
| Weight                    | 28.602                     |
| EAN                       | 0883450134811              |
| Product Group             | M06288                     |
| Number of Mounting Holes  | 4                          |
| Mounting Method           | V Lock                     |
| Housing Style             | 4 Bolt Square Flange Block |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel                 |
| Expansion / Non-expansion | Expansion                  |
| Mounting Bolts            | 7/8 Inch                   |
| Relubricatable            | Yes                        |
| Insert Part Number        | 22226                      |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid              |
| Pilot Configuration       | No Pilot                   |
| Inch – Metric             | Metric                     |

|                                       |   |
|---------------------------------------|---|
| Long Description                      | 4 Bolt Square Flange Block;<br>115MM Bore; 315MM Bolt Circle;<br>222.25MM Bolt Spacing; 1 Piece<br>Solid; V L |
| Other Features                        | Double Row   Single Nut   |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.80   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Weight / LBS                          | 63  |
| Nominal Bolt Circle Diameter<br>Round | 12.4 Inch   315 Millimeter  |
| Bolt Spacing                          | 8.75 Inch   222.25 Millimeter   |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter   |
| D                                     | 5.82 Inch   147.828 Millimeter  |
| d                                     | 4.528 Inch   115 Millimeter   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter   |