ISO HK253514 cylindrical roller bearings

ISO HK253514 cylindrical roller bearings Industries and Applications? We sell 80 mm Shaft Size discount online as well as cheap Mounted Bearing Engineering Group machinery Metric Shaft Size Type parts.

| Engineering Group | Mounted Bearing |
|-------------------------|------------------------|
| Shaft Size | 80 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QVPR19V080SB |
| Locking Style | Single V-Lock |
| Weight | 49.0 lb |
| Housing Style | Four-Bolt Pillow Block |
| UPC Code | 0883450060219 |
| Dimension A | 3.75 in |
| Dimension B | 7.69 in |
| Dimension C | 4.9 in |
| Dimension D Max | 11.25 in |
| Dimension D Min | 9.25 in |
| Dimension E | 2.38 in |
| Dimension F | 13.63 in |
| Dimension G | 3.7500 in |
| Dimension H | 1.56 in |
| Dimension J (Bolt Size) | 0.750 in |
| Dimension L | 4.19 in |
| Dimension RV | 0.29 in |
| Dimension SV | 3.69 in |

| CO — Static Load | 99000 lb |
|-------------------------------------|-----------|
| C — Dynamic Load (Basic) | 86600 lb |
| e — Geometry Factor | 0.23 |
| Y1 - Geometry Factor | 2.88 |
| Y2 - Geometry Factor | 4.29 |
| Oil Lubrication — M/N Seal | 1300 rpm |
| Oil Lubrication — T Seal | 2200 rpm |
| Oil Lubrication — B/C/O Seal | 1000 rpm |
| Grease Lubrication — M/N Seal | 1300 rpm |
| Grease Lubrication — T Seal | 1800 rpm |
| Grease Lubrication — B/C/O Seal | 950 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0030 in |
| Eng Internal Radial Clearance — Min | 0.0043 |
| Eng Internal Radial Clearance — Max | 0.0055 |
| Pre Install Clearance Min | 0.0043 in |
| Pre Install Clearance Max | 0.0055 in |