

# ISO HK2824 cylindrical roller bearings

ISO HK2824 cylindrical roller bearings with easy-to-use parts graphics, giving you the ability to 3461 lb radial static load capacity: check parts availability, pricing, examine remanufactured 1.4375 in d options.

|                               |  |
|-------------------------------|--|
| d                             | 1.4375 in                                    |
| radial static load capacity:  | 3461 lb                                      |
| bolt circle diameter:         | 4.1300 in                                    |
| seal type:                    | Triple Lip with Flinger                      |
| B                             | 5.0000 in                                    |
| length through bore:          | 1.78 in                                      |
| bore type:                    | Round  |
| finish/coating:               | Uncoated                                     |
| duty type:                    | Standard Duty                                |
| maximum rpm:                  | 4500 RPM                                     |
| mounting type:                | Four-Bolt Piloted                            |
| lubrication type:             | Lubrication Fitting                          |
| housing material:             | Cast Iron                                    |
| series:                       | 207  |
| locking device:               | Set Screw                                    |
| standards met:                | UL, AFBMA, AGMA, ASMMA, BSA, CMA, MPTA, PTDA |
| expansion type:               | Non-Expansion Bearing (Fixed)                |
| manufacturer catalog number:  | 076067                                       |
| radial dynamic load capacity: | 5759 lb                                      |