

# ISO HM212046/11 tapered roller bearings

170 Million used ISO HM212046/11 tapered roller bearings instantly searchable. Shop our large selection of parts TIMKEN Manufacturer Name based on 0.0 Inventory brand, price, description, and location. Order the with stock ...

|                          |               |
|--------------------------|---------------|
| Inventory                | 0.0           |
| Manufacturer Name        | TIMKEN        |
| Minimum Buy Quantity     | N/A           |
| EAN                      | 0883450507578 |
| Weight / US pound        | 0.01          |
| Product Group            | M06110        |
| Shaft Size               | 3.4375 in     |
| Shaft Size Type          | Imperial      |
| Weight                   | 45 lb         |
| UPC Code                 | 0883450507578 |
| Type E Open Cover Number | EUDR-3 3/16   |
| Dimension B              | 5 in          |
| Dimension L              | 13-1/2 in     |
| Dimension A              | 4-1/2 in      |
| Dimension J Min.         | 10-3/4 in     |
| Dimension J Max.         | 11-1/4 in     |
| Bolt Diameter            | 3/4 in        |
| Dimension N              | 15/16 in      |
| Dimension N1             | 1-3/16 in     |
| Dimension N2             | 2-3/8 in      |
| Dimension H1             | 2-1/4 in      |

|  |   |
|--|---|
| Dimension H2   | 7-1/2 in  |
| Dimension d1   | 5-17/32 in  |
| Dimension H  | 3-3/4 in  |
| Dimension Ac   | 5.8 in  |
| Dimension d2   | 6.7 in  |
| e  | 0.50  |
| X (if $F_a/F_r \leq e$ )                                   | 0.87  |
| Y (if $F_a/F_r \leq e$ )                                   | 1.71  |
| X (if $F_a/F_r > e$ )                                      | 0.7   |
| Y (if $F_a/F_r > e$ )                                      | 2.07  |
| K Factor   | 1.19  |
| C90 Dynamic Load Rating <sup>1</sup>                       | 19600 lb  |
| C0 Static Load Rating                                      | 108600 lb   |
| Fa-max Maximum Permissible Thrust Load <sup>2</sup>        | 5181 lb   |
| Fr-max Maximum Allowable Slip Fit Radial Load <sup>3</sup> | 16000 lb  |
| Max. Speed <sup>4</sup>                                    | 1640 rpm  |
| Note   | Note: All units have a 1/8 pipe thread grease fitting<br>The Maximum Permissible Thrust Load applies to |